

Project : Genève - avenue de l'Amandolier  
15-17

Order number : KST300/124407

Delivery date : 31.01.2026

TML Group

Frazione Favale

CIVITELLA DEL TRONTO

Ref	Description	Unit price	Quantity	Discount	Total
Sanitary accumulat or 2000 liters on ring, in AISI316L	Sanitary accumulator 2000 liters on ring, in AISI316L Uninsulated diameter : 1 200 mm Total height : 2 040 mm Tipping height : 2 126 mm Ground clearance : 100 mm Internally and externally stained and passivated Operating pressure : 6,00 bar Test pressure : 9,00 bar Temperature : 109 °C Fittings : 1 x revision flange Ø300/380 2 x threaded fitting Rp2" with bend pipe for eau chaude / froide 1 x threaded fitting Rp2" with baffle plate for circulation 1 x threaded fitting Rp2" with bend pipe for brassage 2 x threaded fitting Rp2" with loading spray tube for charge aller 2 x threaded fitting Rp2" with bend pipe for charge retour 1 x threaded fitting Rp¾" for purge 1 x threaded fitting Rp¾" for vidange 3 x threaded fitting Rp½" with thermomètre, 0-120° C, L=200, D=100 3 x threaded fitting Rp½" with pour sonde(s) sans ces dernière(s) avec doigt(s) de gant Connection layout freely configurable Insulation 120mm NEODUL	5'745.00	2	%	11'490.00

Ref	Description	Unit price	Quantity	Discount	Total
Sanitary accumulat or 2500 liters on ring, in AISI316L	Sanitary accumulator 2500 liters on ring, in AISI316L Uninsulated diameter : 1 200 mm Total height : 2 480 mm Tipping height : 2 552 mm Ground clearance : 100 mm Internally and externally stained and passivated Operating pressure : 6,00 bar Test pressure : 9,00 bar Temperature : 109 °C Fittings : 1 x revision flange Ø300/380 2 x threaded fitting Rp2" with bend pipe for eau chaude / froide 1 x threaded fitting Rp2" with baffle plate for circulation 1 x threaded fitting Rp2" with bend pipe for brassage 2 x threaded fitting Rp2" with loading spray tube for charge aller 2 x threaded fitting Rp2" with bend pipe for charge retour 1 x threaded fitting Rp¾" for purge 1 x threaded fitting Rp¾" for vidange 3 x threaded fitting Rp½" with thermomètre, 0-120° C, L=200, D=100 3 x threaded fitting Rp½" with pour sonde(s) sans ces dernière(s) avec doigt(s) de gant Connection layout freely configurable Insulation 120mm NEODUL	6'295.00	2	%	12'590.00
Ded	Estimation dédouanement	2'400.00	1	%	2'400.00
TRANS	Estimation transport	2'500.00	1	%	2'500.00
				<b>Total</b>	<b>28'980.00</b>